

MyLock 744D



It's sew easy with Janome

JANOME

MyLock 744D

Superb Quality in Professional Performance

Upper k Slide the the uppe again, sin

Upper knife retraction lever

Slide the lever to the left to disengage the upper knife action. To engage again, simply slide lever to the right.

BONUS Instruction Video

WyLock 744

Packed in carton

Features

Easy upper knife retraction lever

Lay-in tension dial

Free arm & flat bed convertible

Easy rolled hem changeover

Cutting width 3.1mm - 7.3mm

Differential feed ratio 0.5-2.2

Seam type: 2, 3 and 4 thread overlock

Colour coded thread guides

Lower looper easy threading mechanisms

Optional attachments



Lay-in tension dial

The concealed threading path assures easy to follow threading and stable sewing results.


Free arm & flat bed convertible

Free arm & flat bed type of convertible overlock machine.



2 thread overlocking

For rolled hem stitch with thick thread, flat lock stitch, and when overlocking stretch or lightweight fabrics.



Easy rolled hem change-over


No need to change the needle plate for rolled hemming. Just slide the needle plate setting knob to "R" position to convert the plate for rolled hemming.



Differential feed

The differential feed device is designed to prevent fabrics from puckering or stretching. Both stitch length and differential feed dials can be set at any time, even while sewing.

Range of differential feed ratio



Stretched edges on knit fabrics are prevented by setting the differential feed dial between 1.0 and 2.2.

Puckered edges on fine woven fabrics are prevented by setting the differential feed dial between 0.5 and 1.0.

JANOME

AUSTRALIA

Janome Sewing Machine Co. (Aust) Pty. Ltd. P.O. Box 1383, Moorabbin 3189 Victoria www.janome.com.au

NEW ZEALAND

Janome Sewing Machine Co. (NZ) Ltd.

P.O. Box 139, Dunsandel, Mid Canterbury, New Zealand www.janome.co.nz



AVAILABLE FROM YOUR EXPERT JANOME RETAILER